

Features

- 14-inch color television set with remote control
- Multisystem (TV broadcasts and video playback systems – PAL/SECAM B/G, D/K; AV systems – PAL, SECAM, NTSC - 3.58 MHz/ 4.43 MHz)
- Frequency Synthesize Tuning (FST) (which provides the capability of tuning one TV program on several different channels)
- I2C bus control
- Built-in digital comb filter (NTSC) (for ensuring purer picture with brighter colors)
- 255 channels memory (VHF, UHF and CATV)
- CATV ready
- Automatic and manual program tuning (manual program tuning in both directions)
- Convenient and easy controlling the TV set through the on-screen display (OSD) menu system
- Russian/English/etc OSD
- Direct program choice
- "Recall" function (switching between last and current programs)
- Teletext
- Comprehensive IN/OUT system:
 - 1 x AV stereo IN
 - 1 x SCART
 - 1 x headphones jack
 - 1 x RF
- 4 pre-set picture modes
- 4 pre-set sound modes
- Equalizer
- Sleep timer
- Wake timer
- "Child lock"
- Automatic noise reduction and blue background in the case of none TV signal
- Automatic turning the TV set into "stand by" mode in 5 min after finishing the TV program translation

ORION®

14 inch STP1451



Technical characteristics

Tube	
Dimension	14 inch (37 cm)
Systems	
TV broadcasts and video playback systems	PAL/SECAM B/G, D/K
AV systems	PAL, SECAM, NTSC - 3.58MHz/ 4.43MHz
Channels	
Channels (tuners frequencies)	VHF(L): 46.25-168.25MHz; VHF(H): 175.25-463.25MHz; UHF: 471.25-863.25MHz
Channels (CATV)	Mid band: X- Z, S1- S10; Super band: S11- S20; Hyper band: S21- S41
No of channels	255
Channels indication	Screen display
On-screen display, sound output, automatic switching off	
On-screen display language	Russian/ English/etc
Sound output	2 x 1 W
Automatic switching off durations	15...60 min, interval 15 min
Inputs and terminals	
Radio frequency (RF) antenna input	75 Ohms (un-balanced)
Video/audio terminals	
Video input	1 Vp-p, 75 Ohms
Audio input	≥200 mV (effective), ≥70 kOhms
Power consumption and power supply	
Maximum power consumption	60 W
Power supply	220 VAC, 50 Hz (110-240 VAC, 50-60 Hz)
Accessories	
Remote Controller with 2 batteries	1 pc
Antenna	1 pc
User's Manual and Warranty Card	1 pc
Dimensions and weight	
Dimensions (W. X H. X D.)	4112 mm X 368 mm X 330 mm
Weight (net)	10,5 kg